



IN THE
UNITED STATES
PATENT AND TRADEMARK OFFICE

3635 \$
#14
7/22/03

IN RE APPLICATION OF: Torsten Heinemann

CASE: OST-011218

SERIAL NO.: 09/939,295

FILED ON: August 24, 2001

FOR: COVERING ARRANGEMENT
FOR A BUILDING, AND
COVERING PART FOR USE IN
SUCH A COVERING
ARRANGEMENT

STATEMENT OF
BASIS FOR
RELEVANCE OF
FOREIGN LANGUAGE
DOCUMENTS
IDENTIFIED IN
SUBMITTED
SUPPLEMENTAL
PTO-1449

COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, VA 22313-1450

ATTENTION OF:
Art Unit 3635
EXAMINER:
McDermott, K.

Dear Sir:

If any charges or fees must be paid in connection with the following communication, they may be paid out of our Deposit Account No. 50-0545.

RECEIVED

JUL 0 9 2003

GROUP 3600

Applicant submits that the filing of the accompanying supplemental information disclosure statement is after the period specified in paragraph (b) of 37 C.F.R. 1.97. Accordingly, Applicant respectfully submits the enclosed supplemental information disclosure statement along with the fees as outlined in 37 C.F.R. 1.17 (p).

07/08/2003 CNGUYEN 00000028 09939295

01 FC:1806

180.00 OP

FACTOR & PARNTERS, LLC
1327 W. Washington Blvd., Suite 5 G/H
Chicago, IL 60607
(312) 226-1818
(312) 226-1919 (fax)

Jody L. Factor
Jacob D. Koering

34157
51890

<u>Publication Number</u>	<u>Publication Date</u>	<u>Basis for Relevance</u>
FR 2 655 078	May 31, 1991	Roofing tiles comprise a rigid core of an insulating material enclosed in a film of a tough, flexible material, preferably polyethylene or polypropylene. Preferably comprises an injected phenolic resin foam. Preferably one end of the tile is curved over and features a channel and an underlying small integral stud or rib to engage a slotted lip at the other end of an adjacent tile. The underside of the tile is also provided with slots or channels to engage studs or rails on a supporting batten.
DE 25 14 981	October 14, 1976	The wide-area roofing tile affords full heat-insulating protection, comprises a metal or plastic sheath which enwraps the heat protection. The batten fitted for attachment to the roof supports members has an upward tilt. This not only reinforces the batten's load-bearing qualities, but also provides a U-shaped configuration for a prefabricated inlay of hard foamed plastic, to be inserted after attachment to the roof support members. This leads to tight sealing, with elimination of the cold bridge which would otherwise remain. The upward tilt may contain a pocket for engagement by a curve on the underside of the element, providing additional sealing of the cross or head joint gap.
DE 2 250 555	April 18, 1974	A prefabricated roofing element has a box-type head portion as well as a box-type base portion. The head portion and the end portion may sealingly interengage via complementary surfaces. Thus increased sealing properties and increased resistance against wind are obtained, while there is no additionally work in arranging the roofing elements on the carrying structure of the roof.


DE 25 25 130	December 18, 1975	Corrugated roof tiles of sheet metal, are designed for structural rigidity and to form an effective barrier to driving rain at overlaps, and embody an upward hair-clip sectioned return on the upper transverse edge and a downward return of approximate 'C' section on the lower transverse edge. The former return dovetails into the latter to form a mechanically keyed overlap. The marriage of the returns forms a weather dissipatory cavity at the joint. The geometry of the detail contrives the springing of the hairclip return into its interlocked position with the major face of the lower tile bearing flush on the railing edge of the upper tile. The detail thus presents a limited entry for driven rain with further gravity bars beyond this initial entry.
DE 25 31 220	February 3, 1977	The function of the snow retainer is to prevent slippage of snow on sloping roofs, especially on roofs covered with flat files or pantiles. The retainer comprises a shaped-section piece with a sharply projecting enter piece. This is adjoined on both sides by fishplates, one of which incorporates an end section facing upwards at approximately 90 degrees. The center piece can be A shaped, as viewed from the side. On a pantile roof the retainer can be set so that the upward facing end section fits under the edge of a tile above it, while the latter overlaps the tile on which the retainer lies.

Should anything further be required, a telephone call to the undersigned at (312) 226-1818
is respectfully invited.

Respectfully submitted,

Dated: _____

6/30/03



Jody L. Factor
One of Attorneys for Applicant

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited with the
United States Patent Postal Service as first class mail in an envelope
addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450
on 6/30/03.

Jody L. Factor

Name of Applicant, assignee, applicant's attorney or Registered Representative



Signature